Anchor Channels Product Catalogue HAZ-CI-EN/10.15



Your Fixing Systems Specialist

Anchor Channels Product Catalogue

















Contents

Company Profile	1
HMPR-CE Anchor Channels Introduction	3
ETA - European Technical Approval	5
Product Verification according to ETA	6
HMPR-CE Anchor Channels Systems Product Range	7
HMPR-CE Anchor Channels Standard Lengths	9
HMPR-CE Anchor Spacing & Minimum Edge Distances	10
HMPR-CE Installation detail & section views	11
HMPR-CE Marking & Material grade	12
HMPR-CE Compatable T head Bolt Dimensions	13
HMPR-CE Compatible T head Bolt Load Properties	14
HMPR-CE Anchor Channels Load Tables	15
HMPR-CE Anchor Channels Overview	16
HMPR-CE Anchor Channels Dimensioning Principles	17
Methods of Verification Against Failures	18
Quality Assurance Control	19
HMPR-CE Installation Information	21
Special Types of Anchor Channels	23
Anchor Channels for Metal Decks	25
Anchor Channels for Balustrades	26
HAZ-TU Anchor Channels for Profiled Sheets Introduction	27

HAZ-TU Anchor Channels Product Details	28
HAZ-TU Anchor Channels Technical Details	29
HPTR-SL Self Locking Anchor Channels Product Details	30
HCPLS Anchor Plates Product Details	30
HMCI Concrete Inserts Introduction	31
HWT Wall Tie Introduction & Details	33
HWT-M Wall Ties Introduction	35
HBTR Brick Tie Channel Product Details	35
HWT-M Wall Ties For Masonry Product Details	36
HTB T Bolts & HMLN Lock Nuts Introduction	37
HTB T Bolts & HMLN Lock Nuts Technical Details	39
Anchor Channel Application Examples	41
Support Brackets for facade applications	43
Box channel solution for Facade Applications	45
Anchor channel application pictures	46
Project References	47





HAZ Metal is certified with integrated management systems by TUV SUD for ISO 9001, ISO 9001 & OHSAS 18001

HAZ Metal Sanayi ve Ticaret A.S. All rights reserved. October 2015. Reproduction and distribution of the information contained in this catalogue is forbidden Without prior written consent. HAZ[®] Copyright.



Company Profile

Introduction

HAZ Metal A.S. is located in Iskenderun, in the southern part of Turkey, based in their own property of 17.000 square meters .

The company provides services in the design and production of fixing systems for facade cladding, framing channel systems, brick support systems, cast-in channels and a variety of products used in construction.

The company's mission statement is to assist and advise its clients in choosing the most suitable fixing systems for their requirements and to provide them with quality production and supply with timely deliveries.

The innovative design and production techniques offer practical and economic solutions to solve every possible problem within the scope of fixing applications in construction.

As a manufacturer of fixing systems to major projects around the world, HAZ Metal has proven its quality and reliability to its clients. The company enjoys serving the sector and works hard to constantly improve and develop its services.

HAZ Metal is dedicated to achieving the highest level of customer satisfaction and is always in constant contact with its clients in order to better understand their requirements and to offer the services required for design and production of fixing systems.

Channel Production

The production of cast in channels has been made in HAZ Metal since the year 2001.

Throughout the years, production techniques and methods have been improved to achieve higher quality and productivity. Haz Metal today implements modern technology in the production of channels in order to meet the requirements of the industry.

The factory channel production unit is equipped with a coil slitting machine, channel roll formers, press breaks and production units with 250 ton eccentric presses used for the pressing of the studs on to the channels. There is also an in house electro-galvanizing pool where 12 micro thick zinc coating on mild steel is made. Hot dip galvanizing with over 50 micro thick zinc coating is made by prequalified sources.

The presence of a work shop with the capability of preparing and maintaining the required moulding and tooling, provides flexible production. The urgent preparations, maintenance, revision and adjustment of machines and tooling are made without interrupting the production process which leads to saving time and costs.

The production is strictly controlled with periodic in house testing of both raw materials and finished products, in order to maintain the performance of HAZ products and to fulfil the safety requirements for use in the construction industry.









Production Capacity

HAZ Metal is capable of producing a minimum of three thousands six hundreds metric tonnes of cast in channels yearly.

Roll forming technology is used to produce cold roll formed channels. Anchor studs are cold forged with bolt maker machines. Swaging of the anchor studs on to the channels is done with fully automated lines to achieve the highest quality standards.

To achieve the highest quality standards in our production, most of the production is made with fully automated lines, PLC systems that has significant precision and accuracy, so as to reduce human errors.

The factory is one of the only manufacturer which produces it's own dies and moulds. This ensures high quality and flexibility with results in high competitiveness in pricing and lead time.

Technical Know-How

HAZ Metal has a dedicated and professionally trained team which emphasizes in improving the efficiency and effectiveness of their production.

Technical training is conducted regularly to ensure that technical know-how of the production and engineering processes persists within the organization

Quality Standards

HAZ Metal adopts EN standards in the production of channels. Production is strictly controlled in accordance with these standards.

To achieve its objectives and maintain high level of consistency, HAZ Metal adopts the highest international standards and global best practice.

The company quality management system complies with the requirements of ISO 9001:2008. A quality assurance system and controlled checks are documented in the manufacturing process.



Coil slitting line



22 stand channel rolling machine



16 stand channel rolling machine



Automated stamping unit





HMPR-CE Anchor Channels - Introduction

HMPR-CE Anchor Channels are rolled channels with swaged studs that are used for connections made to concrete structures. This system allows easy and safe fixations to structures such as concrete slabs, beams and columns.

HTB T head bolts and HMLN lock nuts to allow secure and easy connections on to anchor channels. The use of this system is applicable in a wide range of construction works.

Features of HMPR-CE cast in channels are as follows:

• HMPR-CE Anchor Channels are designed in accordance with the design rules according to CEN / TS 1992-4-3.

• HMPR-CE Anchor Channels allow users working with low edge distances.

• Load resistances can be improved by using higher concrete strenght class on loading.

• Shear and tensile resistance in concrete can be improved with additional reinforcement.

HMPR-CE Anchor Channels are manufactured by HAZ Metal A.S. in Turkey with engineering and product development provided from its siter company in Germany, HAZ Deutschland GmbH. Since 2004 HAZ Metal has built an effective product development system to increase the integrity of its products and production.

HMPR-CE channels have been tested in IFBT Leipzig in accordance to the EOTA guidelines and have received good results. The HMPR-CE cast in channels have been awarded an ETA certificate.

HMPR-CE anchor channels can be used safely and efficiently with the following features:

- Quality production with strict control according to European requirements
- Management and Service quality certified by ISO 9001:2008
- Euro code compatible design and product dimensioning using product selection software
- Customized design in providing solutions to meet special product requirements





HMPR Cold rolled cast in channels

• HMPR-S Toothed, cold rolled cast in channels

• HMPR-H Hot rolled cast in channels

З

HMPR-CE Anchor Channels - Introduction



Advantages

- No drilling on site
 Quick and easy fixing
- Fixing without damaging concrete
- Adjustable and flexible
 Safe near edges on
- concrete

 High load capacity
- Fixing without electrical tools
- Safe and secure fixing
- No dust particles falling onto facade
- No electricity needed
- Easy connections with T head bolts and lock nuts
- Compensation of tolerances
 of the structure
- Fixtures are removable and new fixing can be made

Planning

Careful planning needs to be done prior to concrete casting. Anchor channel types should be determined according to the load capacities, edge distances, area of applications etc. Anchor channel positioning should be incorporated in to the shop drawings of the form works in order to provide clear instructions for installation on site.

Brick walls are installed using special support brackets that are fixed on to anchor channels using T head bolts. A continuous anchor channel embedded into the concrete wall provides high adjustability and enables quick installation of the masonry brackets. Anchor channels cover the load capacity requirements for the masonry facade installation.



The prefabricated concrete industry is among the fastest growing fields within the construction industry. The use of Anchor channels enhance the fast and economical solutions that are offered using prefabricated concrete panels. Speed and security are the benefits of using Anchor channels.





Applications

Anchor channels are widely used for the installation of curtain walls. Unitised panels with materials such as glass and natural stone already incorporated are preassembled in to the curtain wall panels. These panels are erected on to the facades and are quickly and easily fixed on to anchor channels using T head bolts and special brackets.



Anchor channels are used for a variety of construction applications which require attachments made on to concrete. Pipe and duct installation and the installation of electrical wiring are the most common applications that are made using anchor channels.



ETA - European Technical Approvals

European Technical Approval ETA

5

In June 2013 HMPR-CE anchor channels have been certified with an ETA certificate from DIBT (German Institute of Building Technology). HMPR-CE anchor channels are Euro code compatible that are designed and dimensioned according to CEN/TS 1992-4 standard in combination with the approved loadings in the HAZ ETA approval. The channels that are dimensioned according to CEN/TS 1992-4 standard are distinguished with a code HMPR-CE and the products are stamped with the CE marking.

The ETA approval includes thorough specifications on internal and third party quality control of on-going production. Therefore quality assurance is in place to be certain that the quality of the HMPR-CE channels correspond with the samples tested during the approval procedure.

European Standard CEN/TS 1992-4

The European CEN standard has been created for the purpose of standardising the dimensioning of fastenings in to concrete structures. Any connections in to concrete such as anchor bolts and anchor channels are regulated with this standard.

CEN/ TS standards committee for the Design of fastenings for concrete was founded in 2000. In 2009 the set of regulations were published as CEN/TS 1992-4. This technical specification document is treated as a preliminary standard with an objective to turn in to a European standard. With the publication of this standard a representation of advanced fixing technology is used in practice.

Benefits of using HMPR-CE Anchor Channels

A comprehensive test program is conducted on the products in accordance to the new guidelines of ETA. Channels are wet tested to consider failure loads on channels, studs and concrete in various situations such as load direction and reduced edge distances.

With the resistance loads derived from extensive testing, greater flexibility is achieved in the design of connections into concrete. Regarding whether the concrete is reinforced or non-reinforced, cracked or uncracked, load carrying connections can be provided. Therefore numerous options are achieved which influence the results. These values can be used to achieve the most economic and effective solution for the application at hand.

The advantages of the HMPR-CE channels can be summarized as below:

- · Possibility to consider various concrete strength classes
- Recognizing reinforcement when designing the location of the anchor channel
- Highest cost effectiveness in choosing the most effective selection
- · Small edge distances are possible with verified loadings
- Increased loads with additional or closely positioned reinforcements
- Optimised design by taking into account concrete strength, reinforcement lay out and component thickness.

ETA - European Technical Approval



The European Technical Approval ETA- 13/0399 for the HMPR-CE Anchor Channels was issued by the Deutsches Institut für Bautechnik (DIBt) in 2013. This new approval is valid on all states of Europe.

This ETA catalogue includes the dimensioning of the anchor channels in accordance with the new European standards series CEN/TS 1992-4-3 "Design of fastenings for use in concrete - Anchor Channels".









Product Verification Method according to ETA

CEN-TS 1992-3 Standard

CEN TS/1992-4 part 3 standard lays down a newly developed method for the design and dimensioning of anchor channels. The verification guideline is shown in the following table.

Verifications for HMPR-CE anchor channels acc. to CEN/TS 1992-4-3					
Tension Loading			Shear Loading		
Failure Mode			Failure Mode		
	Anchor	$N^{a}_{Ed} \leq N^{a}_{Rd,s,a}$		Anchor	V ^a _{Ed} ≤ V ^a _{Rd,s,a}
	Connection between anchor and channel	N ^a _{Ed} ≤ N ^a _{Rd,s,c}	Steel Failure	Connection between anchor and channel	V ^a _{Ed} ≤ V ^a _{Rd,s,c}
Steel Failure	Local flexure of channel lip	$N_{Ed} \le N^a_{Rd,s,l}$		Local flexure of channel lip	$V_{Ed} \le V^a_{Rd,s,l}$
	Special screw	$N_{Ed} \le N^a_{Rd,s,s}$		Special screw	$V_{Ed} \le V^a_{Rd,s,s}$
	Flexure of channel	$M_{Ed} \le M_{Rd,s,flex}$	Pry-out failure		$V_{Ed} \le V^a_{Rd,cp}$
Pull-out failure		N ^a _{Ed} ≤ N _{Rd,p}			
Concrete cone failure		N ^a _{Ed} ≤ N _{Rd,c}	Concrete eage railure		v Ed ⊃v Rd,c

On verification table, N_{Ed} and V_{Ed} loads represent design tensile and shear loads of channels which act on the bolt, while $N^a E_d$ and $V^a E_d$ are the loads that result on studs of the channel.

* All proofs of failure types should be checked acc. to verification table.

Dimensioning Software

The new HAZ CCP (Anchor Channel Calculation Program) for calculating HAZ Anchor channels with rules of European Technical Approval (ETA) is a convenient and very powerful tool for users.

With this program, users will be able to design channels in a few seconds concerning with various parameters such as concrete grade, small edge distances, additional reinforcements, loads types and so on. That would require an optimum design for the user.





HMPR-CE Anchor Channels - Product Range

HMPR - Cold rolled anchor channels



HMPR Cold rolled channels are suitable to with stand static loads. The range available can cover resistance loads ($N_{Rd} = V_{Rd}$) between 7,22 kN and 50,56 kN. Channels are available in stainless steel 1.4301 & 1.4401 and hot dip galvanised mild steel 1.0038 & 1.0976 (S235JR & S355MC).

Product Code	HMPR-CE 72/49	HMPR-CE 54/33	HMPR-CE 49/30	HMPR-CE 40/25	HMPR-CE 38/17	HMPR-CE 28/15
Channel Section	72/49	54/33	49/30	40/25	38/17	28/15
Load Capacity (kN) N Rd = ^V Rd Steel / Stainless steel	45.00/50.56	41.67/36.67	17.22/25.00	12.22/15.00	10.56/12.22	7.22/8.33
Channel Flexure (Nm) Steel / Stainless steel ^M Rd,s,flex	9868/6408	2832/2696	1646/1600	1356/1048	595/651	349/348

Product Code	HTB-72	HTB-54	HTB-50	HTB-40	HTB-38	HTB-28
Metric size	M20,M24,M30	M12,M16,M20	M12,M16,M20	M10,M12,M16	M10,M12,M16	M8,M10,M12
T.Bolt min spacing (mm) S _{SIb}	121	80	74	64	47	41

7

HMPR-H Hot rolled Anchor Channels - Product Range

HMPR-H

Hot rolled cast-in channels



HMPR-S Cold rolled toothed cast-in channels



HMPR-H Hot rolled channels are suitable to with stand dynamic loads as well as static loads. These channels are available in hot dip galvanized and mild steel finish 1.0038 (S235JR).

HMPR-S Cold rolled toothed channel 41/22 can be used for longitudinal loads. This channel is available in stainless steel 1.4301 & 1,.4401 and hot dip galvanised mild steel 1.0038 (S235JR).

Product Code	Juct Code HMPR-H 52/34		HMPR-H 40/22
Channel Section	52/34	50/30	40/22
Load Capacity (kN) N Rd = ^V Rd Steel / Stainless steel	30.5/ -	17.2/	11.1/ -
Channel Flexure (Nm) Steel / Stainless steel ^M Rd,s,flex	3226/ -	2703/ -	1260/ -

Product Code	HTB-72	HTB-54	HTB-50
Metric size	M20,M24,M30	M12,M16,M20	M12,M16,M20
T.Bolt min spacing (mm) S _{SIb}	81	73	58

HMPR-S 41/22	
41/22	
15.8	
595 / 651	

HTS-41	
M12,M16	
28	



HMPR-CE Anchor Channels - Standard Lengths

Standard Channel Lengths

The list of the standard product range is showed on the table in accordance with European Technical Approval requirements. Other lengths and anchor numbers can be supplied depending on request.

For further information please contact us.

Product Length Range of HAZ HMPR-CE Anchor Channels - Length / Number of Anchors									
Cold Rolled Channels							Hot Rolled Channels		
HMPR 72/49	HMPR-CE 54/33	HMPR-CE 49/30	HMPR-CE 40/25	HMPR-S 41/22	HMPR-CE 38/17	HMPR-CE 28/15	HMPR-H 52/34	HMPR-H 50/30	HMPR-H 40/22
170/2	170/2	150/2	150/2	150/2	100/2	100/2	170/2	150/2	150/2
200/2	200/2	200/2	200/2	200/2	150/2	150/2	200/2	200/2	200/2
250/2	250/2	250/2	250/2	250/2	200/2	200/2	250/2	250/2	250/2
300/2	300/2	300/2	300/2	300/2	250/2	250/2	300/2	300/2	300/2
350/2	350/3	350/3	350/3	350/3	300/3	300/3	350/3	350/3	350/3
450/3	400/3	400/3	400/3	400/3	350/3	350/3	400/3	400/3	400/3
650/3	550/3	550/3	550/3	550/3	450/3	450/3	550/3	550/3	550/3
970/4	820/4	800/4	800/4	800/4	550/4	550/4	820/4	800/4	800/4
	1070/5	1050/5	1050/5	1050/5	850/5	850/5	1070/5	1050/5	1050/5
	3070/13	3050/13	3050/13	3050/13	1050/6	1050/6	3070/13	3050/13	3050/13
	6070/25	6050/25	6050/25	6050/25	3050/16	3050/16	6070/25	6050/25	6050/25
					6050/31	6050/31			
130 ≤ Ss ≤ 400	≤ Ss ≤ 400 100 ≤ Ss ≤ 250				$50 \le Ss \le 200$ $100 \le Ss \le 250$)	
Ss = Anchor spacing									

Standard short length channels

Short lenght channels are available from 100 mm to 950 mm with stud quantities and spacings according to the table above.



Standard long length channels

Long length channels are supplied in 1050, 3030 and 6070 mm lengths with varying stud spacings according to section type of the channel.



Types of round anchors studs

Туре	Anchor	Shaft d1	Head d2	min hef
			[mm]	
	28/15	6	12	45
	38/17	8	16	76
spr	40/25	8	16	79
	49/30	10	20	94
ind St	54/33	12	24	155
Rou	72/49	16	32	179
	40/22	8	16	76
	50/30	10	20	94
	52/34	16	32	156



HMPR-CE Anchor Spacings & Minimum Edge Distances

Anchor stud spacings

In order to meet the resistance loads, anchor stud spacings should be postitioned according to the tables below.

Anchor	Anc Spa	chor cing	End Spacing (x)	min channel length (mm l)	
Channel	smin	smax	round anchor	round anchor	
28/15 38/17	50	200	25	100	
40/25 40/22 49/30	100	250	25	150	
50/30 54/33 52/34	100	270	35	170	
72/49	130	400	35	200	

Side view





Minimum edge distances

Depending on the type of the channels, anchors studs must be positoned at a minimum distance from the component edges.

The minimum spacings of the T head bolts must be adhered to according to the table below.



Anchor Channel			28/15 38/1			38/17		40/25 & 40/22			49/30 & 50/30		54/33 & 52/34		72/49					
Special screws	М		8	10	12	10	12	16	10	12	16	12	16	20	12	16	20	20	24	30
Min. spacing of screws	Ss,min		40	50	60	50	60	80	50	60	80	60	80	100	60	80	100	100	120	150
Min. anchorage dept	min hef	mm		45		76		79		94			155		179					
Min. edge distance	Cmin			40			50			50			75			100			150	
Min. member thickness	hmin						hef + Dh + Cnom													



Installation Details & Section Views

Installation of the anchor channels

The fitness for use of the anchor channel can be guaranteed according to the following installation conditions:

 The installation of the anchor channels must be made with qualified workers

 Installation must be made with the manufacturers specifications and drawings

• Fixing on the form work must be done in a way that no movement of the channels will occur during laying of the reinforcement bars and pouring and compacting of the concrete

 The concrete under the head of the anchor channels must be properly compacted

Size and positioning of the t head bolts must correspond to the specificatiosn and drawings

Setting torques of the T head bolts must not be exceeded





Typical Section Views

Legend:

channel	height
	channel

hannel
ł

h_{ef} anchorage depth

h_{nom} Embedment depth







__

11

HMPR-CE Anchor Channels - Product Range

Marking



Material Types

Materials and in	tended use				
	Dry conditions	Internal conditions with usual humidity	Medium corrosion exposure	High corrosion exposure	
Specification	Material types required for use in structures subject to dry internal conditions with the exception of usual humidity (e.g. accomodations, offices, schools, hospitals etc.)	Material types required for use in structures subject to internal conditions with usual humidity (e.g. kitchen, bath and laundry in residential buildings)	Material types required for use in structures subject to external atmospheric exposure (including industrial and marine environment) or in permanently damp internal conditions.	Material types required for use in structures subject to exposure in particular aggressive conditions (e.g. immersion of sea water, chloride atmosphere) or atmosphere with chemical polution (e.g. in desulphurization plants)	
Channel material grade	Steel 1.0038;1.0044 EN 10025 hot-dip-galv ≥ 50 um	Steel 1.0038;1.0044 EN 10025 hot-dip-galv ≥ 50 um	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088	
Anchor material grade	Steel 1.0038;1.0214,1.0401 1.1132,1.5525 EN 10263 hot-dip-galv ≥ 50 um	Steel 1.0038;1.0214,1.0401 1.1132,1.5525 EN 10263 hot-dip-galv ≥ 50 um	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088	
T head bolt material grade	Steel strength grade 8.8/4.6 EN ISO 898-1 e-galv ≥ 5 um	Steel strength grade 8.8/4.6 EN ISO 898-1 hot-dip-galv ≥ 50 um	Stainless steel 1.4401/1.4404/1.4571 1.4362, EN 3506-1	Stainless steel 1.4462/1.4529/1.4547 EN 3506-1	
Washer material grade	Steel EN 10025 e-galv ≥ 5 um	Steel EN 10025 hot-dip-galv ≥ 50 um	Stainless steel 1.4401/1.4404/1.4571 EN 10088	Stainless steel 1.4462/1.4529/1.4547 EN 10088	
Nut material grade	Steel strength grade 8.8 EN 20898-2 e-galv ≥ 5 um	Steel strength grade 8.8 EN 20898-2 hot-dip-galv ≥ 50 um	Stainless steel 1.4401/1.4404/1.4571 EN ISO 3506-2	Stainless steel 1.4462/1.4529/1.4547 EN ISO 3506-2	
1) Available on re	quest				

2) Steel acc. to EN 10025, 1.0038 not or anchor channels 28/15 and 38/17

3) Electroplated acc. to EN ISO 4042

4) Hot-dip galvanized on the basis of EN ISO 1461, and coating thickness \geq 50 μ m



13

HMPR-CE Anchor Channels - Product Range

Dimensions of the HAZ METAL Special Screws & Strength Grade



Dimensions of the HAZ METAL Special Screws:

				Length		
Anchor Channel	Fig.	b1	b2	k	F	I
onanioi			[mm]			
29/15	1	10	23	4	8	15-200
20/15	1	10	23	5	10	20-300
	1	13	31	6	8	20-300
20/17	1	13	31	6	10	20-300
38/17	1	13	31	7	12	20-300
	1	13	31	7	16	20-300
	2	14	35	7,5	8	20-300
40/25	2	14	35	7,5	10	20-300
	2	14	34	8,5	16	20-300
	2	13	43,3	10	10	20-300
49/30	2	13	43,3	10	12	20-300
54/33	2	17	43,3	11	16	20-300
	2	21	43,3	12	20	30-300
	2	23	58	14	20	50-300
72/49	2	25	58	16	24	50-300
	2	31	58	20	30	50-300

Special Screws	Stee	_{el} 1)	Stainless Steel ¹⁾			
Strength grade	4.6	8.8	A4-50	A4-70		
f _{uk} [N/mm ²]	400	800	500	700		
f _{yk} [N/mm ²]	240	640	210	450		
Finish	z.p.,	h.d.g				

1) Materials according to Annex 3, Table 1



I erf = Bolt length

- i = channel lip thickness
- t fix = Fixture thickness
- s = washer thickness
- V = minimum thread length

• The length of the T bolt must be determined using the formula (L erf =tfix + i + f + v)

Dimensions V_{min}

T head bolt Metric size	V _{min} (mm)
M8	12.5
M10	14.5
M12	17.0
M16	20.5
M20	26.0
M24	29.0
M30	33.5

Dimensions of channel lip f

Anchor Channel	f (mm)
28/15	2.25
38/17	3.00
40/25	5.60
49/30	7.39
54/33	7.90
72/49	9.90

T head Bolt Load Properties

T head bolts characteristic load values





T Head Bolt		M8	M10	M12	M16	M20	M24	M30
max fixture hole dia. (mm)		9	12	14	18	22	26	33
	N _{Rd}	7.3	11.6	16.9	31.4	49.0	70.6	112.2
4.6	V _{Rd}	5.3	8.3	12.1	22.6	35.2	50.7	80.6
	M _{Rd}	9.0	17.9	31.4	79.8	155.4	268.9	538.7
	N Rd	19.5	30.9	44.9	83.7	130.7	188.3	299.2
8.8	V _{Rd}	11.7	18.6	27.0	50.2	78.4	113.0	179.5
	MRd	24.0	47.8	83.8	213.1	415.4	718.4	1439.4
	N _{Rd}	6.4	10.1	14.8	27.4	42.8	61.7	98.1
A4-50	V _{Rd}	4.6	7.3	10.6	19.8	30.9	44.5	70.7
	M _{Rd}	7.9	15.7	27.5	70.0	136.3	235.8	472.5
	N Rd	13.7	21.7	31.6	58.8	91.7	132.1	210.0
A4-70	V _{Rd}	9.9	15.6	22.7	42.2	66.0	95.1	151.0
	MRd	8	33.5	58.8	149.4	291.3	503.7	1009.2

Minimum spacing and setting torque of T head bolts



General: The fixture is braced to the concrete and channel respectively. The stated torque values must not be exceeded.



Steel to steel: The fixture is braced to channel with use of a suitable washer. The stated torque values must not be exceeded.

Cost in	THood		Setting Torque Tinst						
Channel	Bolt Diameter	Ss,min	General	Steel-steel contact 8.8	Steel-steel contact A4-70				
	M8	40	8	20	20				
28/15	M10	50	13	40	40				
	M12	60	15	50	50				
	M10	50	15	40	40				
38/17	M12	60	25	70	70				
	M16	80	45	100	120				
	M10	50	15	40	40				
40/25	M12	60	25	70	70				
	M16	80	45	150	150				
	M12	60	25	70	50				
49/30	M16	80	60	180	180				
	M20	100	75	90	190				
	M12	60	25	70	50				
54/33	M16	80	60	180	180				
	M20	100	120	120	320				
	M20	100	120	360	-				
72/49	M24	120	200	360	-				
	M30	150	380	400	-				



HMPR-CE Anchor Channels Load Tables

Tensile / Single Loading



Shear - Single Loading



Tensile - Pair Loading



Shear - Pair Loading



- -		stance		Resistance Load FRd (kN) Tensile loads a>15° / Single Loads									
anne	je dis (mm)	mpor imur knes		Channel length (mm) / no of anchor studs									
Ч ^Ч СР	⊢ ⊢ Pol	Mir edç ar (ji ti i C	150 (2)	200 (2)	250 (2)	300 (2)	350 (2)	350 (3)	1050			
28/15	M8,10,12	65	100	6.5	6.9	6	-	-	6.9	5.6			
38/17	M12,16	100	130	10.5	10.5	10.3	-	-	10.5	8.3			
40/25 40/22	M16	130	150	12.2	12.2	12.2	12.2	-	12.2	7.4			
49/30 50/30	M16,20	195	180	17.2	17.2	17.2	17.2	-	17.2	9.3			
54/33 52/34	M20	260	250	39.5	40.8	41.1	41.3	-	39.8	13.9			
72/49	M24,30	325	300	-	44.8	44.9	44.9	44.9	-	17			

_	e ead imum imum mm)		m stance m ss h		Resistance Load FRd (kN) Shear loads a<15° / Single Loads								
anne			mpor knes	Channel length (mm) / no of anchor studs									
4 Ch		Mir edg ar (mi tric Co	150 (2)	200 (2)	250 (2)	300 (2)	350 (2)	350 (3)	1050			
28/15	M8,10,12	65	100	6.5	6.9	6	-	-	6.9	5.6			
38/17	M12,16	100	130										
40/25 40/22	M16	130	150	12.2	12.2	12.2	12.2	-	12.2	7.4			
49/30 50/30	M16,20	195	180	17.2	17.2	17.2	17.2	-	17.2	9.3			
54/33 52/34	M20	260	250	39.5	40.8	41.1	41.3	-	39.8	13.9			
72/49	M24,30	325	300	-	44.8	44.9	44.9	44.9	-	17			

		n stance	n n is h	Resistance Load FRd (kN) Tensile loads a>15° / Pair Loads								
anne	fead	je dis mm)	mpor imur knes	Channel length (mm) / no of anchor studs								
, g ⊾	⊢ q	Mir edg ar ((mr nic O	200 (2)	250 (2)	300 (2)	350 (2)	350 (3)				
28/15	M8,10,12	65	100	4	-	4.3	-	4.3				
38/17	M12,16	100	130	6.6	-	6.8	-	7.2				
40/25 40/22	M16	130	150	8.6	8.8	-	-	9.2				
49/30 50/30	M16,20	195	180	13	13.4	-	-	13.7				
54/33 52/34	M20	260	250	20.9	21.3	-	-	21.5				
72/49	M24,30	325	300	27.2	27.7	-	28.1	-				
	Maximur	n t bolt spacing	g s min (mm)	100	125	125	150	150				

_		n stance	n n ss h	Resisdence Load FRd (kN) Shear loads a<15° / Pair Loads								
anne	fead	je dis (mm)	mpor knes	Channel length (mm) / no of anchor studs								
Ч ^Ч СЧ		Mir edg ar (mi tric	200 (2)	250 (2)	300 (2)	350 (2)	350 (3)				
28/15	M8,10,12	65	100	4	-	4.3	-	4.3				
38/17	M12,16	100	130	6.6	-	6.8	-	7.2				
40/25 40/22	M16	130	150	8.6	8.8	-	-	9.2				
49/30 50/30	M16,20	195	180	13	13.4	-	-	13.7				
54/33 52/34	M20	260	250	20.9	21.3	-	-	21.5				
72/49	M24,30	325	300	27.2	27.7	-	28.1	-				
	Maximum t bolt spacing s min (mm)			100	125	125	150	150				

15

HMPR-CE Anchor Channels Overview

				Cold rolled	d channels			Hot	rolled chanr	nels
Profiles		HM PR 72/49	HM PR-CE 54/33	HM PR-CE 49/30	HM PR-CE 40/25	HM PR-CE 38/17	HM PR-CE 28/15	HM PR 52/34	HM PR 50/30	HM PR 40/22
Section view	Section view									
Material		A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	A2/A4/HDG	HDG	HDG	HDG
Bolt Type	Bolt Type		HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ	HS/HAZ
Bolt	Bolt		50/30	50/30	40/22	38/17	28/15	50/30	50/30	40/22
М	М		10*-12-16-20*	10*-12-16-20*	8*-10-12-16	8*-10-12-16	8-10-12	10*-12-16-20*	10*-12-16-20*	8*-10-12-16
S _{slb} [mm]		121	80	74	64	47	41	81	73	58
			Desig	n Resistance	e Capacities	of Profiles (Design valu	es)		
$N_{Rd,s,l} = N_{Rd,s,c}$; [kN]	[kN] 45 4		17.2	12.2	10.6	7.2	30.6	17.2	11.1
V _{Rd,s,I} [kN]	45	41.6	17.2	12.2	10.6	7.2	30.6	17.2	11.1
M [Nm]	HDG	9868	2832	1646	1179	517	303	3226	2703	1260
WRd,s,flex [NTT]	St.St.	6408	2696	1600	911	566	302	2696	1600	911
					Geometric v	alues				
b _{ch} [mm]		72	54	49	40	38	28	52	50	40
h _{ch} [mm]		49	33	30	25	17	15	34	30	22
h _{nom} [mm]]	182	157	96	81	78	47	158	96	78
h _{ef} [mm]		179	155	94	79	76	45	156	94	76
c _{min} [mm]		150	100	75	50	50	40	100	75	50

Cold rolled profile









HMPR-CE Dimensioning Principles

Required information for channel selection

The information below are required to conduct a full analysis in order to dimension and select the most secure and suitable anchor channel for the fixing application:

Anchor channel type & Type of raw material

17

- · Anchor channel lenght with munber of studs and stud spacing distances
- · Positioning of the cast in channel in the concrete component with exact edge distances of the channel on all directions
- Thickness of the concrete component and the strenght classof the concrete
- · Allocation & layout of reinforcement bars within in the concrete component
- · Type and size of t head bolts and their numbers
- Fixture application dimensions &type of fixing whether top of slap or edge of slab
- Tensile and shear loadings on the fixture

Verification areas when selecting a cast in channel

The assessmet of the suitable anchor channel dimensions for the intended use with regards to the requirements of the mechanical resistance, stability the safety of the application is done by checking the following areas.

Verifications under tension loads								
1. Distribution of acting tension loads								
2. Steel failure - anchor stud	N _{Rk,s,a}							
3. Steel failure - t head bolt	N _{Rk,s,s}							
4. Steel failure - connection between channel & anchor stud	N _{Rk,s,c}							
5. Steel failure - local flexure of channel lips	N _{Rk,s,I}							
6. Steel failure - flexure resistance of channel	$M_{Rk,s,flex}$							
7. Steel failure - trasnfer of setting torque into prestressing force	T _{inst}							
8. Concrete failure - pullout	N _{Rk,p}							
9. Concrete failure - concrete cone	N _{Rk,c}							
10. Concrete failure - splitting due to installation	$C_{_{\min}},S_{_{\min}},h_{_{\min}}$							
11. Concrete failure - splitting due to loading	N _{Rk,sp}							
12. Concrete failure - blow out	N _{Rk,cb}							
13. Reinforcement	$N_{_{Rk,re}}$, $N_{_{Rd,a}}$							
14. Displacement under tension loads	σ _N							

Verifications under tension loads							
1. Distribution of acting shear loads							
2. Steel failure without lever arm- t head bolt	V _{Rk,s,s}						
3. Steel failure without lever arm - flexure channel lips	V _{Rk,s,I}						
4. Steel failure with lever arm	M ⁰ _{RK,s}						
5. Concrete failure - pry out	VRk,cp						
6. Concrete failure - concrete edge	V _{Rk,c}						
7. Reinforcement	V _{Rk,c,re}						
8. Displacement under shear loads	σ						

Methods of Verification Against Failures

Anchor channel verification against steel breakout

- Correct channel selection by comparing allowable loads and applied loads
- Determination of the anchor loads from tensile loads and shear forces according to the load influence model verification of the connection between anchor and channel
- Arrangement of the bolts along the channels length





Ĩ

Breakout of chanel lips under tensile loading



Breakout due to flexure of channel under tensile loading



Breakout of T head bolt under shear loading



Breakout of channel lips under shear loading

Concrete verification against failures

Breakout of channel stud

under tensile loading

- Thickness of the concrete component
- Strength class of the concrete
- Condition of the concrete, cracked or non cracked as a special case to be verified
- Verification against concrete edge distance and channels spacings









Failure of concrete edge under shear loading



Pull out of channel from concrete under tensile loading



Failure of concrete pry out under shear loading





Blow out of concrete under tensile & shear loading



Quality Assurance Control

HAZ Metal readily embraces the responsibility of the business that it is in. The company has established a well planned quality management system and has been awarded the ISO 9001:2008 quality management certificate.

This system is a part of HAZ Metal's operations and there are no exceptions or compromises in jeopardising the level of quality of the products under production. The QAC department is staffed with knowledgeable and experienced engineers who are trained in the field and form the backbone of this operation.

The factory is equipped with testing machines which are used to conduct chemical and physical tests on all items that enter and exit the warehouse. The production is strictly controlled with periodic in house testing of both raw materials and finished products. This procedure is a part of day to day operations in order to maintain the performance of HAZ products and to fulfil the safety requirements for use in the construction industry.

1.)

150 kN standing tensile load testing machine. Mechanical testing for manufactured products are carried out using this machine

2.)

Mechanical testing laboratory with computer aided operations to prepare internal reports and record test results

3.)

Spectrometer is used for conducting chemical composition analysis for the raw materials and the end product components that are sourced outside production

4.)

100 kN mobile anchor tensile load testing machine. Testing for performance of products on substrates are carried out using this machine

5.)

6.)

Galvanized coating micro thicknesses are checked using electronic gauges to ensure that corrosion protection is in place for steel products

Material thicknesses are checked using digital micrometers to ensure that the products are produced according to tolerance thicknesses













Quality Assurance Control

Testing procedures have been formulated and are implemented to make sure that the production of cast in channels meet the required standards.

Production

HAZ Metal produces cast in channels since 2001. Modern production lines, innovative tools, and a high production volume guarantee high quality and a reliable delivery terms.

Quality assurance

The quality assurance system developed by HAZ Metal forms the basis for all interests in the production that is certificated by safety standards authority German Institute TUV SUD for Standardization EN ISO 9001:2008.

Own department, consisting of specially qualified engineers, supervises every working step - in the production, as well as in the service area - around the ISO 9001:2008 and the strict application of the totally quality plan that is put through by HAZ management.

Factory-owned production control

As a component of the mentioned measures to the quality assurance system, a factoryowned test lab provides for the constant quality checks of the cast in channels. The ready products, as well as the raw materials are tested by a constant and uncompromising control system.

The factory-owned production control is directed with the strict guidelines for the protection of the quality after the test plan of the DIBt which is an obliging component of the universal appraisal licensing.

Foreign supervision

An independent and authorized testing laboratory is appointed for the supervision of the production according to the licensing and the matching test plan of the DIBt. The cast in channels are marked after the certification of the independent testing institute which has awarded HAZ with the compliance mark (Ü sign).



External Testing - conducted by independent test laboratory



Internal Testing - conducted in house





HMPR Anchor Channels - Installation Information

Load Direction

21



Installation Instruction



1.) Anchor channels are fixed to form work after careful planning and positioning. Concrete is then cast in to the form work.



2.) After the concrete is cured, the filler inside the channel, set for the purpose of preventing concrete filling the channel's slot, is removed as shown.



3.) Connections to the cast in channels are made with T bolts and lock nuts. T bolts are inserted in to the channels horizontally and then turned right through 90 degrees. This locks them vertically in the channel.



4.) Fixtures are fastened with the T bolts and nuts as shown above. Correct loading and torque values need to be applied in accordance with the allowable loads of the channels and bolts.

HMPR Anchor Channels - Installation Information

Length Cutting At Construction Site

Standard long lengths can be cut to size on construction sites according to the desired length. Care should be taken in making sure that the minimum distance of 25 mm between the studs and channel end should be met.



· An end anchor is available to be fixed at the end of the cut channel to avoid wastage.





· Long lengths can be cut to size providing the X size is no less than 25 mm.

Attachment To Form Work

It is important to firmly attach the anchor channels on to form work. There are a few ways to execute this important procedure which is made onto wood and steel form work.

· Fixing onto wood form work using nails.



· Fixing onto steel form work using pop rivets.



Removing The Strip Filler

Anchor channels are supplied with strip fillers within the open slot of the channels to prevent concrete ingress. This strip filler is removed as shown after the concrete is cured.



· Fixing onto wood form work using staples.



· Fixing onto steel form work using T bolts.



Connections To Channels

Fixtures are attached on to the anchor channels with T head bolts and lock nuts. There are suitable types for each Anchor channel section.

· Fixing T bolts into channels.





Adjustability

T bolts are suitable to be inserted at the desired point along the length of the channel. Fixing is done by turning the T bolt 90 degrees clockwise and by tightening the nut. The correct torque values must be applied when tightening the nuts. T bolts must not be located beyond the last stud which is 25 mm from the end of the channel.



• Suitable T bolts can be inserted at desired point • To ensure correct installation of the T bolt the • T bolts must not be positioned and adjusted easily along the length of the channel. notch at the end of the shank must be checked. beyond the last stud on the channel.



HMPR-SP Special Types of Anchor Channels

Anchor Channels With Reinforcement Studs

Anchors can be manufactured out of reinforcement studs for special applications, particularly fixings in the edge of thin slabs. These channels have higher pull out loads and combined loads. Due to these qualities these channels are preferred for use in the fixing of curtain walls on to reinforced concrete beams.







Channels With Special Fabricated Elements

Special anchor channel manufacturing can be made according to the requirements of the project. Local testing as well as in house testing can me made to safe check the load capacities of the special anchor channels.





23

HMPR-SP Special Types of Anchor Channels

Curved Anchor Channels

Channels can be easily curved to an internal or external radius (lips inward or lips outward). Curves on elevation, such as brick arch details, which require special care, can be accommodated with these types of channels.



Outside channel slot



Min Rodius	Channel Types											
Will. Radius	28/15	38/17	41/22	40/25	40/22	49/30	50/30	54/33	52/34			
Inner channel - Ri	0.5 m	0.5 m	1.5 m	1 m	0.7 m	0.8 m	0.8 m	4 m	0.8 m			
Outer channel - Ra	1.0 m	1.5 m	4 m	3 m	2 m	8 m	4 m	0.8 m	4 m			

Channel Pair - Special Fabricated Unit

Where double or multiple fixings are required at known centres, channels can be welded to spacer straps, as shown below. The straps keep the channels parallel and accurately spaced along their length.



Corner Fabricated Unit

Channels can be easily fabricated to suit corners, see below. (Smaller channels may be folded; larger channels are welded.)

• Standard leg dimensions are 125 mm by 250 mm. Other sizes can be produced upon request.

 Available in stainless steel and hot dip galvanized mild steel.

Channels With Wing Strip

Wing anchors are available for low profile details, e.g. where a channel is located in the concrete casing of a steel beam. The channel load capacity is reduced.





Channels With Strap Strip

If a narrow beam has a central reinforcement bar, anchors can be made to pass each side of the bar. This might occur where fixings for mechanical services are required in waffle slabs.



HMPR-MD Anchor Channels for Metal Deck Connections

The use of concrete cast on metal decking is being used more commonly in the building industry. Fixing of exterior facades such as curtain-walls, masonry walls, precast panels etc, are often required to be connected close to the edge of the metal deck. The metal deck anchor channels have good performance in thin slabs and in perimeter locations. The special designed assemblies made on the back of the channels provide strong bond with the concrete, when they are located within the reinforcement cage. Loads applied on the channel spreads over a longer area around the length of the slab edge. The workmanship of through deck fixing can be significantly reduced. The channels are easily placed before pouring the cement, with the channel studs or lugs of any suitable length to clear the ribs in the metal deck. Channels for metal decks are usually produced in hot dip galvanized mild steel. However, stainless steel grade 1.4301 and 1.4401 are also available upon request.







25

HMPR-BL Anchor Channels for Balustrades

HMPR-BL anchor channels are the cold rolled channels with welded re bars. The HMPR-BL channels are used for fixing balustrades and hand rails on to the front faces of decks and balcony slabs. The re bars with stamped heads guarantee safe loading when fixing on thin slabs. The welded re bars are made our of ST500 build steel with ribs.

Advantages

- Fully adjustable
- Reduces significantly the construction time
 Permits adjustment and replacement of attached structures
- Can be used even on thin front faces of less than 100 mm
- T Head bolts are used instead of welding or anchor bolts





Product Code	Length L (mm)	Stud Diameter Sd (mm)	Stud Length SI (mm)	T Head Bolt Size	Product Code	Length La/Lb (mm)	Stud Diameter Sd (mm)	Stud Length SI (mm)	T Head Bolt Siz e
	100							201	M10
HMPR-BL-38/17	150	10	201	M12x50 & M16x60	HMPR-BL-38/17	170/170	12		M12x50 & M16x60
	200								
	100		90 M12x50 & M16x60					M10yE0.8	
HMPR-BL-40/25	150	10		M12x30 &	HMPR-BL-40/25	170/170	14	90	M12x50 &
	200								
	100			M12x50.8	HMPR-BL-49/30		14	150	M12x50.8
HMPR-BL-49/30	150	12	110	M12x50 &		170/170			M12x50 &
	200								
	100		4 200	M10yEO 8		170/170	14	250	MIDVED
HMPR-BL-54/33	150	14		M12x50 & M16x60	HMPR-BL-54/33				M12x50 &
	200								

Product Code



Material:

A2: Stainless steel 1.4301,

A4 Stainless steel 1.4401,

HDG hot dip galvanized mild steel 1.0038 (S235JR) (Studs are always out of steel BST 500S)







HAZ-TU Anchor Channnels for Profiled Metal Sheeting - Introduction

HAZ-TU Anchor channels for profiled metal sheeting installation on reinforced concrete beams and columns are available in 3 and 6 mm thicknesses and 60/22 sections.

Fixing is done with self drilling screws or shot fired nails. Channels allow fast and economical installation as this system eliminates the difficult and time consuming anchor fixing into concrete.

Channels are inserted onto the surface of the concrete component flush to the surface and in the correct alignment. The end joints between channels should be minimum 20 mm. Fixing to the channels is made with either self drilling screws 6.3x22 or shot fired nails 4.5x24.

Channels are available in two standard types in 3 metre length with foam filling. Available materials are stainless steel grade 1.4301 (AISI 304) & 1.4401 (AISI 316) and hot dip galvanized mild steel.



• Fixing metal profiled sheets on to HAZ-TU anchor channels using self tabbing screws



• Cladding material attached at the EDGE of the component





HAZ-TU anchor channels are casted in to concrete components



Cladding material attached at the TOP of the component

HAZ-TU Anchor Channels for Profiled Metal Sheets - Product Details



HAZ-TU Cast in channels for profiles metal sheet installations are supplied in either 3 or 6 mm thicknesses. A foam filler is inserted in the open slot of the channel for preventing inflow of wet cement during casting. There are studs welded on to the channel for strong connections on to the concrete. There are three different stud versions which offer different results for loads and minimum edge spacings. Channels are supplied in Stainless steel and hot dip galvanized mild steel.



• The installation of profiled metal sheets on to prefabricated concrete components with embedded HPTR channels enables easy and economical fixing.



• Fixing is done with self drilling screws on to the HPTR cast in channels, without the need of pre-drilled holes. Power screw driver with 1500 rpm is required for fixing.



• HPTR channels are cast flush to the surface. The concrete surface should be trowelled smooth enabling the metal sheets to be positioned directly over the channels.



• Drilling positioning should be made in the middle of the channels, leaving a minimum distance 1/3 of the width from the side of the channel.



• The minimum edge spacing (ae) should be no less then 20 mm. The distance (x) between the channel end the screw position should be no less than 25 mm.



• The minimum spacing (ar) between channels should be 20 mm.



HTPR Cast-in Channels - Technical Details



	Technical Details							Tensile - Max Design Load Capacity F _{ED} kN			
Product Code	Length	Channel Thickness	Section	Execution	No Of Studs	Stud Spacing	Stud Edge Distance	F Ld F Ld F Ld=S	Ed F F F F Ld=S/2	F S S F	
								Single Loads	Pair Loads	Evenly distibuted load	
HAZ-TU 60/22/3-C2 HAZ-TU 60/22/3-C3	3000	3	60/2:2	A	16 40	450 150	75	4.6 7.0	2.5	15.5 46.6	
HAZ-TU 60/22/6-C2 HAZ-TU 60/22/6-C2	3000	6	60/2:2	в	16 40	450 150	75	7.0	2.5	15.5 46.6	
HAZ-TU 60/22/3-B2 HAZ-TU 60/22/3-B3	3000	3	60/22	A	16 40	450 150	75	4.6	2.5	15.5 46.6	
HAZ-TU 60/22/6-B2 HAZ-TU 60/22/6-B2	3000	6	60/2:2	в	16 40	450 150	75	7.0	2.5	15.5	
HAZ-TU 60/22/3-A2 HAZ-TU 60/22/3-A3	3000	3	60/22	А	8 20	450 150	75	4.6	2.5	15.5 46.6	
HAZ-TU 60/22/6-A2 HAZ-TU 60/22/6-A2	3000	6	60/2:2	в	8 20	450 150	75	7.0	2.5	15.5 46.6	

Values are for concrete strength class C20/25

Self drilled screws must be capable to support the indicated loads

Set screws should be positioned in the central third of the channels width and no closer than 25 mm to channels end

Product Code			Edg	e Dista	nces (m	m)		
HAZ-TU-60/22/3-C2-3000		а	ar	ae	af	d	b	dj
								ae
Length	Type HAZ-TU C	200	120	20	20	240	68	
Size	Type HAZ-TU B	200	100	20	20	200	75	ar
Туре	Type HAZ-TU A	200	100	20	20	200	100	b aa ar
								V d

Execution 2 : Can be cut into two pieces at the centre. Edge spacing must be minimum 75 mm.



Execution 3 : Can be cut into multiple pieces at the centre of two studs. Minimum edge space must be 75 mm.



37

HTPR-SL Self Locking Cast-in Channels - Product Details

HTPR-SL type cast in channels are self locking channels for connections that are light weight. These channels are ideal for attachments of rails, metal cladding, window & door frames on to concrete substrate. Channels are available in pre-galvanzied steel.









	iechnical Details											
Product Code	Dimensions			Loadings		Edge Spacings						
	Length (mm)	Thickness (mm)	Section (mm)	Safe load (kN)	Load Spacing (mm)	aa (mm)	ar (mm)	ae (mm)	af(mm)	d (mm)		
HPTR-SL/40	3000	2.5	40/25			140	70	20	20	25		
HPTR-SL/60	3000	2,5	60/25	1.3	250	160	80	20	20	25		
HPTR-SL/80	3000	3.0	80/25			180	90	20	20	25.5		

Values are for concrete strength class C20/25

Self drilled screws must be capable to support the indicated loads

· Load indicated is suitable for tensile, shear and resultant load

HCPLS Cast-in Plates - Product Details

HCPLS Cast-in plates is a product that offers solutions for attaching steel components to concrete substrates. Cast-in plates are cast in to the concrete with a flush surface. Corresponding steel or stainless steel elements are welded to the surface of the cast in plates. These elements are supplied in stainless steel and steel.

The allowable loads for the cast in plates for tensile, shear and bending moments are verified on project basis according to the required design criteria.

Product Details									
Plate Sizes	Pate Thicknesses	Stud Diameters	Stud Lengths						
		6	50						
70/100,		8	50						
100/140,	4, 6, 8, 10, 12	10	75						
160/160,	10, 12	12	100						
		16	125						

Cast-in plates with 4 & 2 studs with flush surface suitable for welding

Cast-in plates with 4 & 2 studs with tabbed holes suitable for attachments with screws

Cast-in plates with 4 & 2 studs with welded threaded bars for attachments with hex nuts





HMCI Concrete Inserts - Introduction

HMCI concrete inserts are produced from 41/41 & 41/21 C channels with pressed out strips that are punched out at 100 mm centres. These channels are used for casting in to concrete to enable connections without drilling. Various applications for connections to floors, walls, and ceilings are made for the installation of secondary structures. HMLN lock nuts can be inserted anywhere along the length of the channels. The channels are supplied with an easily removable strip, which prevents the ingress of grout and cement. Concrete inserts can be supplied in electro galvanised, hot dip galvanised and stainless steel finishes.

Advantages

- * No Drilling
- * Fast and easy fixing
- * No need for electricity
- * No dust when constructing.
- * Economic through less workmanship



Installation Instruction



1.) HMCI concrete inserts are nailed on to the form work at the required location, prior to casting of the concrete.



2.) After the concrete has dried, then the filler is removed by using a screw driver or similar tool.

3.) Fixing is done at the desired position along the length of the channel. Installation is made with lock nuts and set screws.

The strips pressed out of the back of the HMCI concrete inserts are designed to provide positive anchoring in to the concrete. Distortion of the pressed strips is not recommended as it will severely reduce the performance of the insert. HMCI concrete inserts are either point welded or wired to steel reinforcement. HMCI concrete inserts are supplied with a filler to prevent the ingress of grout and cement in to the channel slot.

HMCI Concrete Inserts - Product Details

HMCI-41/21 Concrete Insert

6.7 kN pull out admissible load per 300 mm span





HMCI-41/41 Concrete Insert

8.8 kN pull out admissible load per 300 mm span





Code	Size	Length
HMCI-41/21	2,5x41/21	6000
HMCI-41/41	2,5x41/41	6000

M6, M8, M10, M12 size lock nuts are used for fastening fixtures on to the concrete inserts.
Standard stock lengths are 6000 mm. Special length fabrication can be made upon request.
Material: A2: Stainless steel EN 1.4301, A4 Stainless steel EN 1.4401, HDG hot dip galvanized mild steel 1.0038 (S235JR), EG Electro galvanized mild steel 1.0038 (S235JR).



HWT Wall Ties - Introduction & Product Details

The HWT Wall ties provide secure and easy connections between concrete components. Serrated ties and washers enable safe transmittal of tensile loads.

Wall ties are used with cast in channels and T head bolts to achieve three dimensional adjustability for restraining attachments of prefabricated concrete components.

Wall ties are available in stainless steel 1.4301 & 1.4401 and hot dip galvanized W 1.0038 grade steel.





HWT - Wall Tie







Product Code	-+ 20 (K mm)	(C mm)	(2)	all.F (kN)	(ar mm)	(mm)
HWT - 28 -50	50	0	90			
HWT - 28 -75	75	25	115			
HWT - 28 -100	100	50	140			
HWT - 28 -125	125	75	165	3.5	50	11x55
HWT - 28 -150	150	100	190			
HWT - 28 -175	175	125	215			
HWT - 28 -200	200	150	240			

(Lmm)

Slotted

Hole

Distance

Load

•To be used with HMPR-28/15 channels and HTB-28/15-M10x40 T Bolts.

tion -+ 20

Product Code

HWT - 38 - 75	75	0	115			
HWT - 38 - 100	100	25	140			
HWT - 38 - 125	125	50	165			
HWT - 38 - 150	150	75	190	7.0	75	13x55
HWT - 38 - 175	175	100	215			
HWT - 38 - 200	200	125	240			

-+ 20

•To be used with HMPR-38/17 channels and HTB-38/17-M12x50 T Bolts.

33

HWT Wall Ties - Product Details







Product Code	P (ł	Projec- tion -+ 20 K mm)	Cavity -+ 20 (C mm)	Length (L mm)	Tensile Load all.F (kN)	Edge Distance (ar mm)	Slotted Hole (mm)
HWT-B-28-75		75	25	115	_		
HWT-B-28-125		125	75	140	3.5	50	11x55
HWT-B-28-150		150	100	190			
HWT-B-28-175		175	125	215			
•To be used with HMPR-	28/15	channe	els and HT	B-28 M10x	40 T Bolts		,

HWT-B-38-100	100	25	145			
HWT-B-38-125	125	50	165	7.0	75	40.55
HWT-B-38-150	150	75	195	7.0	75	13x55
HWT-B-38-175	175	100	220			

•To be used with HMPR-38/17 channels and HTB-38 M12x50 T Bolts.

HWT-U Wall Tie







•To be used with HMPR-49/30 channels and HTB-49 M16x60 T Bolts.



HWT-M Wall Ties for Masonry & MAS Brick Tie Channel Introduction

HWT-M Wall ties for masonry are used for the safe and easy connections of masonry blocks to the wall through connections made to cast in channels or surface fixed framing channels.

HWT-M type wall ties are designed for restraint attachments of both masonry wall facades and masonry walls to load bearing walls. The sliding concrete capability of the ties along the length of the channels decreases the risk of the masonry cracking due to structure movements.

The wall ties are inserted on the channel at desired points and are positioned by turning the ties 90 degrees clockwise. The perforated holes in the wall ties allow mortar filling to improve bonding.

Wall ties for masonry are available in stainless steel 1.4301 (AISI 304) & 1.4401 (AISI 316).

MAS-25/15 Brick tie channels are cold rolled pre-galvanized channels that have punched lugs on the back of the channels. This channel provides the same loading performance as the 28/15 and is an economic option for use in restraining brick walls on to concrete.

Lugs are punched out every 250 mm and the channels are supplied with a strip filler.

A debonding sleeve is used as a cover for the wall ties. This enables the wall tie to accomodate longitudinal movement in the direction of the tie. This is ideal when installing long masonry walls to concrete walls or when tying in large span infill walls to floor slabs. Debonding sleeves allow room for movement and prevents any cracking of the masonry walls.



HWT-M Wall Tie





· Wall ties can be used for masonry wall connections fixed to load bearing walls. Embedding length (e) is achieved with the length of the wall tie.



MAS-25/15 **Brick Tie Channel**

wall tie (L) and the masonry block width (d).



· Lugs are prepunched on the back of the channel at 250 mm centres. The lugs are easily bent out on site prior to the casting of concrete.



· Wall ties are easily inserted into the debonding sleeves before installation is made.

35

HWT-M Wall Ties for Masonry - Product Details



• HWT wall ties can be used with cast in channels type 28/15 and 38/17.

HWT-MS - Wall Tie



HWT-MV - Wall Tie



HWT-ML - Wall Tie



HWT-MT - Wall Tie





 Connections on to surface fixed HMP channels type 28/15 and 38/17 can also be made.



• HMP channels can be welded on to structural steel to allow wall tie connections.

Product Code	Length (mm)	Thick- ness (mm)	Width (mm)	Channel Type	Tensile Load (Kn)	Shear Load (Kn)
HWT-MS 28 -85 HWT-MS 28 -120 HWT-MS 28 -180	125 185 245	1.25 1.25 1.25	25 25 25	28/15	2.5	1.4

Product Code	Length (mm)	Thick- ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
	95	2	26			
1001-1010 20 - 05	00	2	20			
HWT-MV 28 -120	120	2	26	28/15	3.2	2.7
HWT-MV 28 -180	180	2	26			
HWT-MV 38 - 85	85	2	30			
HWT-MV 38 -120	120	2	30	38/17	3.2	2.7
HWT-MV 38 -180	180	2	30			

Product Code	Length (mm)	Thick- ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
		1				
HWT-ML 28 - 85	85	3	25			
HWT-ML 28 -120	120	3	25	28/15	3.2	2.7
HWT-ML 28 -180	180	3	25			
HWT-ML 38 - 85	85	3	30	00/17		
HWT-ML 38 - 120	120	3	30	38/17	3.2	2.7

HWT-ML 38 - 7 HWT-ML 38 - 7

		-		20/10	0.2	
80	180	3	25			
85	85	3	30	00/47		
120	120	3	30	38/17	3.2	2
180	180	3	30			

Product Code	Length (mm)	Thick- ness (mm)	Width (mm)	Channel Type	Tensile Load (kN)	Shear Load (kN)
	05	-	05			
HW1-M1 28 - 85	85	3	25			
HWT-MT 28 -120	120	3	25	18/15	3.2	2.7
HWT-MT 28 -180	180	3	25		-	
HWT-MT 38 - 85	85	3	30			
HWT-MT 38 -120	120 3 30 38/17		38/17	3.2	2.7	
HWT-MT 38 -180	180	3	30			



37

HTB T Bolts & HMLN Lock Nuts - Introduction

HTB T bolts & HMLN lock nuts for attachment in to cast in channels are specially designed for a perfect fit into the section of the channels. Insertion is made and after a 90 degree turn clockwise the fixing is made. Correct torque values must be applied in order to achieve secure connections.

T bolts and lock nuts are available in stainless steel 1.4401 and hot dip galvanised steel strength class 4.6 & 8.8.





Fixing Instructions



1.) After pouring of cement, the concrete wall should be left to dry



5.) Suitable T head bolts should be inserted into place by placing the narrow side of the head in the slot



2.) After concrete has dried out, the filler in the channel should be taken out using a suitable tool



6.) Locking in place will be done when turning 90 degrees. Notch on the shank must be set vertically



3.) The filler can be pulled out along the length of the channel simply by hand



7.) T head bolts can be adjusted along the length of the channel to be in the desired position



 No filler or concrete left overs should be left within the channel slot. Any residue should be scrapped out



8.) When the connection has been made recommended torque must be used in order to fasten the T bolts

HTB T Bolts & HMLN Lock Nuts - Technical Details

Thead					Loa	ding Table	e for T He	ad Bolts ((kN)					Max 1	Forque	Loads	(Nm)
Bolt	Grade	4	.6 Class S	teel	8	.8 Class S	steel	S 1	tainless S .4401 / A4	teel -50	Stainless Steel 1.4401 / A4-70			4.6 Class	8.8	1.4401/	1.4401/
Size	Loads	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load	Tensile & Shear	Bending Moment	Longitudi- nal Load	Steel	Steel	A4-50	A4-70
M 6	all.F F _{Rd}	2.2 3.1	2.0 2.8	0.10 0.14	:	-	-	2.2 3.1	1.8 2.5	0.1 0.1	3.0 4.2	3.8 5.3	0.1 0.2	3	-	3	4
M 8	all.F F _{Rd}	4.0 5.6	5.0 7.0	0.20 0.28	:	-	:	4.0 5.6	4.4 6.2	0.2 0.3	5.5 7.7	9.4 13.2	0.3 0.4	8	-	8	10
M 10	all.F F _{Rd}	6.4 9.0	10.0 14.0	0.30 0.42	13.3 18.6	24.9 34.9	1.1 1.5	6.4 9.0	8.7 12.2	0.3 0.4	8.7 12.2	18.7 26.2	0.4 0.6	15	48	15	20
M 12	all.F F _{Rd}	9.3 13.0	17.5 24.5	0.50 0.70	19.4 27.2	43.7 61.2	1.6 2.2	9.3 13.0	15.3 21.4	0.5 0.7	12.6 17.6	32.8 45.9	0.7 1.0	25	70	25	35
M 16	all.F F _{Rd}	17.3 24.2	44.4 62.2	0.90 1.26	36.1 50.5	110.0 154.0	3.0 4.2	17.3 24.2	38.8 54.3	0.9 1.3	23.6 33.0	83.3 116.6	1.2 1.7	60	200	60	80
M 20	all.F F Rd	27.0 37.8	86.5 121.1	1.40 1.96	56.4 79.0	216.4 303.0	4.7 6.6	27.0 37.8	75.7 106.0	1.4 2.0	36.8 51.5	162.3 227.2	1.9 2.6	120	400	120	160
M 24	all.F F Rd	38.8 54.3	149.9 209.9	2.00 2.80	81.2 113.7	-	-	38.8 54.3	130.9 183.3	2.0 2.8	-	-	-	200	680	200	-
M 30	all.F F Rd	61.7 86.4	299.9 419.9	3.20 4.48	129.0 180.6	-	-	61.7 86.4	262.4 367.4	3.2 4.5	-	-	-	400	1.400	400	-

	Loading Table For Locknuts (kN)																			
Lock Nut Type		HMLN-28 HMLN-38			HMLN-41			HMLN-40			HMLN-50			F	HMLN-72					
LUCKINU	t type	M6	M8	M10	M8	M10	M12	M6	M8	M10	M12	M8	M10	M12	M10	M12	M16	M12	M16	M20
Safe	all.F	1.9	2.8	3.0	4.0	4.1	5.7	4.0	4.0	6.4	9.3	4.0	6.4	9.3	6.4	9.3	9.3	9.3	17.3	22.0
Load	F _{Rd}	2.7	3.9	4.2	5.6	5.7	8.0	5.6	5.6	9.0	13.0	5.6	9.0	13.0	9.0	13.0	13.0	13.0	24.2	30.8

Motrio		Longitudi	nal Loading On	Toothed Channel			
Size	Grade	Mild	Steel	Stainless Steel			
OIZC	Loads	Longitudinal Load	Max Torque (Nm)	Tensile & Shear	Longitudinal Load		
M 8	all.F	4.0	28.0	4.0	16.0		
M10	all.F	5.0	55.0	5.0	31.5		
M12	all.F	5.0	75.0	5.0	55.0		
M16	all.F	7.5	125.0	5.0	125.0		







39

HTB T Head Bolts - Product Details

					-	te also i a al Dista	9				
Product	r ecrimical Details										
Code	Bolt Size	Metric	Length	Head Thick.	Head Width	Head Length	Sutaible for	Product Drawing			
Coue	mm	M (mm)	L (mm)	a (mm)	b (mm)	c (mm)	Channels	Floduct Diawing			
HTB-28-8/30	M8x30	8	30								
HTB-28-8/50	M8x50	8	50	4.0	10.50	22.0					
HTB-28-10/40	M10x40	10	40			10.50	23.0	TIVIF K-20/10			
HTB-28-10/60	M10x60	10	60								
HTB-38-10/40	M10x40	10	40								
HTB-38-10/50	M10x50	10	50		13.00			and the second se			
HTB-38-10/70	M10x70	10	70								
HTB-38-12/50	M12x50	12	50								
HTB-38-12/60	M12x60	12	60	7.0		30.5	HMPR-38/17	c: 0			
HTB-38-12/80	M12x80	12	80								
HTB-38-16/80	M16x60	16	60								
HTB-38-16/80	M16x80	16	80					D: a: L:			
HTB-38-16/100	M16x100	16	100								

Product				ails						
Code	Bolt Size mm	Metric M (mm)	Length L (mm)	Head thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for Channels	Product Drawing		
HTB-40-10/50	M10x50	10	50							
HTB-40-10/70	M10x70	10	70							
HTB-40-12/50	M12x50	12	50	12.0						
HTB-40-12/60	M12x60	12	60		11.00	24.0	HMPR-40/25,			
HTB-40-12/80	M12x80	12	80		14.00	34.0	HMPR-H-40/22			
HTB-40-16/80	M16x60	16	60							
HTB-40-16/80	M16x80	16	80							
HTB-40-16/100	M16x100	16	100							
HTB-50-12/50	M12x50	12	50		17.50		HMPR-49/30, HMPR-54/33, HMPR-H-50/30, HMPR-H-52/34	a:		
HTB-50-12/60	M12x60	12	60	13.0						
HTB-50-12/80	M12x80	12	80							
HTB-50-16/60	M16x60	16	60			12.0				
HTB-50-16/80	M16x80	16	80			42.0		° Ψ		
HTB-50-16/100	M16x100	16	100							
HTB-50-20/80	M20x80	20	80					b: L:		
HTB-50-20/100	M20x100	20	100							
HTB-72-20/60	M20x60	20	60							
HTB-72-20/80	M20x80	20	80				HMPR-72/49			
HTB-72-20/100	M20x100	20	100	17.0	22.00	58.0				
HTB-72-24/80	M24x80	24	80							
HTB-72-24/100	M24x100	24	100							

Product Code		Technical Details									
	Bolt Size mm	Metric M (mm)	Length L (mm)	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for Channels	Product Drawing			
HTB-41-12/50	M12x50	12	50	10.0	20.00	24.0					
HTB-41-16/60	M16x60	16	60	10.0	20.00	34.0	TIVIF K-3-4 1/22				

Product Code

A4 Stainless steel W 1.4401,

Material:



HDG 4.6 hot dip galvanized steel strenght class 4.6 HDG 8.8 hot dip galvanized steel strenght class 8.8



HMLN Lock Nuts - Product Details

	Technical Details									
Product Code	Metric Size M (mm)	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for Channels	Product Drawing				
HMLN-28-6	6		13.00	24.5						
HMLN-28-8	8	4.0			HMPR-28/15					
HMLN-28-10	10									
HMLN-38-10	10					М				
HMLN-38-12	10	6.0	17.50	31.5	HMPR-38/17	b: / O / a:				
HMLN-38-16	10					c				

Product Code	Metric Size M (mm)	Head Thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for Channels	Product Drawing	
HMLN-40-10	10						
HMLN-40-12	12	10.8	17.00 34.5	34.5	HMPR-40/25,	HMPR-40/25, 34.5	
HMLN-40-16	16			110,22			
HMLN-50-10	10	11.7			HMPR-49/30,		
HMLN-50-12	12		21.0	21.0	21.0 43.5 HMPR-54/33, HMPR-H-50/30.	43.5	43.5 HMPR-54/33, HMPR-H-50/30
HMLN-50-16	16				HMPR-H-52/34		
HMLN-72-12	12					C'	
HMLN-72-16	16	22.0	31.00	62.0	HMPR-72/49		
HMLN-72-20	20						

				Technical de	etails			
Product code	Bolt size mm	Head thick. a (mm)	Head Width b (mm)	Head Length c (mm)	Sutaible for channels	Product drawing		
HMLN-41-6	6	6.0						
HMLN-41-8	8	8.0	20.00	34.0		A R CA		
HMLN-41-10	10	10.0			HIMPR-3-41/22	- Contraction		
HMLN-41-12	12	12.0						
						D b: M		

						C:	a:			
	Technical Details									
Product Code	Bolt Size	Head Thick.	Head Width	Head Length	Sutaible for	Product Drawin	a			
	mm	a (mm)	b (mm)	c (mm)	Channels	r loddor Blawin	9			
HMLN-S-41-6	6	6.0	20.00				0			
HMLN-S-41-8	8	8.0		24.0		Pitto a	())			
HMLN-S-41-10	10	10.0		34.0	TIMF R-3-41/22	and the second	And and			
HMLN-S-41-12	12	12.0								
Product Code										

HMLN - 28 - 6 T

— Metric — Channel type — Type A4 Stainless steel W 1.4401, HDG hot dip galvanized steel



42

HMPR Cast-in Channels - Application Examples



- · Installation of curtain walls
- Installation of natural stone panels
- Installation of masonry walls



· Installation of precast concrete panels



· Connection of concrete beams

Installation of pipe systems

HMPR Cast-in Channels - Application Examples



Installation of base components



Installation of stadium seats



- Installation of pipe systems
- Wall connections

Wall connections



Upper beam connection

Base connection

Lower beam connection



HFSB Facade Support Brackets

Curtain wall facades are used more frequently in the external facade cladding for modern buildings. The curtain wall technology is the most advanced type of facade construction which are preferred because of its aesthetics and functionality. This type of cladding also offers high thermal and load performance and can be installed faster and easier than any other conventional type of claddings.

HAZ Metal designs and manufactures facade brackets for the installation of curtain wall panels on to the structure. HSFB facade support brackets are used to fix longitudinal and transverse curtain wall systems. The brackets transfer the acting loads in to the structure. These brackets can be designed to adapt to any type of application with accordance to the design criteria.

HSFB facade anchors are designed and dimensioned to with stand high horizontal and vertical loads. The facade brackets are available in two main categories.

The first category of facade brackets are the ones that can be fixed on the edge of the slabs. This way the tensile loads from wind are transferred in to the end of the floor slab.

The second category of facade brackets are the ones that are fixed on the top of the slab. This way the horizontal loads from wind and the vertical loads from dead load and the resultant loads are transferred in to the top of the floor slab.

The facade brackets offer great advantages when used with HMPR cast in channels. Both secure and easy connections are enables with the verified load performance values and the high adjustability properties of the HMPR cast in channels.

Advantages

• Simple and fast installation due to the adjustability of the system in all directions

 Smaller edge distances make it possible to fix close to the edge or front end of the floor slabs

 High load performance both for horizontal and vertical loads. Up to 32 kN loads possible

• Can be specially designed and dimensioned to suit various type of fixing applications



Modern high rise buildings



Curtain wall fixing at the edge of floor slab



· Curtain wall fixing at the edge of floor slab

HFSB Facade Support Brackets - Product Range

Application details

•Bracket for installing curtain wall at top of slabs

• Quick and Easy Installation with hang on method

• + / - 10 mm vertical adjustment through incorporated set screws on the bracket

• In and out adjustability through the slotted holes. Fixing at desired point is made with serrated washers

• Lateral adjustability made with on the cast in channel. Fixing is made with two T head bolts

Can be designed to take wind loads of up to 24 kN

Can be designed to take dead loads of up to 7 kN

• Available in stainless steel and hot dip galvanized mild steel



HFSB-AP Facade Support Bracket



HFSB-MT Facade Support Bracket



Application details

•Brackets for installing curtain walls at edge of slabs

• Adjustability made through slot holes. Position fixing is made with serrated washers

• Easy fixing with uncomplicated parts

Available in stainless steel and galvanized steel





HFSB-MT Facade Support Bracket









HAZ-RBX Recess Box Anchor Channels

Unitized curtain systems are often installed at the top of the slab. This creates a problem in which the brackets used to install the curtain wall panels stand out above the finishing line of the floor.

As a result, usable area is reduced and aesthetics is compromised. The use of the HAZ-RBX Recess Box anchor channels, provide a solution for this problem.

The HAZ -RBX anchor channels are supplied with the suitable anchor channel which creates a void in the concrete that allows the bracket to be installed below the finished floor level.

The HAZ-RBX channel is an assembled box made out of galvanized steel or epoxy paint coated steel recess box, that is tack welded with a suitable anchor channel. The type and size of the anchor channel is determined according to the design loads of the curtain wall application.

The box is filled with foam to avoid access of concrete in to the void. There are nail holes on the steel box to allow secure connection of the box on to wooden form work.

After the installation of the HAZ-RBX anchor channels on to the form work is compeleted, concrete is poured leaving the top of the box flush with the concrete pour.

Once the concrete is dried, the foam filler is pulled out and the void is exposed. The curtain wall support bracket is installed on to the anchor channels using t head bolts.

After the installation is finished and the support bracket is tigtened, the void is filled with concrete or grout. The bracket is covered and the void is completely filled leaving a flush finished floor.

Features and benefits:

• The HAZ-BRX Recess box channel is manufactured with tight tolerances

• Dimensions can be customized to application requirements

Nail holes are available for fixing the box to wooden form work

Foam filler is provided with an exact fit to aviod concrete ingress

Anchor channels are tack welded to the recess box

• Corrosion resistant epoxy paint coating or hot dip galvanzing made to the recess box



• HAZ-RBX Recess Box Anchor channels can be supplied with any type of anchor channels



• HAZ-RBX Recess Box Anchor channels are supplied with foam filling to avoid concrete recess in to the void



• HAZ-RBX Recess Box Anchor channels are used for curtain wall installation at the top of the slab



 HAZ-RBX Recess Box Anchor channels can be custom made. The above dimensions (mm) are for HMPR -CE- 49/30-350 type channel

45

Anchor Channels Application Pictures

Anchor chnnels are in all kind of connections in to concrete. All types of facade applications can be executed using anchor channels. This is prefered due to its easy and fast installation. Below are pictures taken from anchor channels applications used in the wide construction applications.







Brick work cladding fixed on anchor anchor channels

Curtain wall cladding fixed on anchor channels on the top of slab









Various anchor channel appications used on areas such as, electric utility, water management and in tunnels



Stadium seating fixed on anchor channels





References



Infinity Tower, Brisbane



Adnoc HQ, Abu Dhabi





The Ruby Tower, Mumbai



Telekom HQ, Ankara



Dolphin Tower, Ankara



Ciftci Towers, Istanbul



Emaar Square, Istanbul



Centre for Technology and Design, St Polten

47

Your Fixing Systems Specialist | 48

References



Ang Mo Kio ITE Headquarters, Singapore



Hyflux Innovation Centre, Singapore



Conrad Hotel, Dubai



Awly Building, Christchurch





Orchard Emerald, Singapore

Dorsett Hotel, Singapore







HAZ Metal is certified with integrated management systems by TUV SUD for ISO 9001, ISO 9001 & OHSAS 18001



HAZ PAZARLAMA İÇ & DIŞ TİC. A.Ş. Sarıkanarya Sok. Ece Apt. No. 8/1 Kozyatağı Mah. 34742 Kadıköy İstanbul, TÜRKİYE Tel : +90 (0) 216 410 72 26 Fax : +90 (0) 216 410 71 41 www.hazpazarlama.com hazpazarlama@hazgrp.com

HAZ INTERNATIONAL LTD. 154 Great North Road Hatfield Herts. AL9 5JN England Tel : +44 (0) 1707 - 260 180 Fax : +44 (0) 1707 - 260 190 www.hazuk.co.uk haz@hazuk.co.uk

HAZ EGYPT LTD 3 Hafez Ramadan St. Nasr City, Cario, Egypt Tel : + 2 (0) 10 447 59 98 www.hazeg.com info@hazeg.com HAZ METAL SANAYİ VE TİCARET A.Ş. Şehit Er Çıracı Caddesi No. 10 Akçay Sanayi Bölgesi 31200 İskenderun Hatay, TÜRKİYE Tel : +90 (0) 326 626 20 50 Fax : +90 (0) 326 626 20 45 www.hazmetal.com info@hazmetal.com

HAZ MARBLE INDUSTRY & TRADE LLC First Gulf Building Corniche Street 2nd Floor, Flat No. 202 P.O. Box 5721 Abu Dhabi, United Arab Emirates Tel : +971 (0) 2 622 07 00 Fax : +971 (0) 2 622 17 00 www.hazuae.ae hazuae@hazmarbleuae.ae

HAZ MARBLE QATAR WLL P.O.BOX 31296 C-Ring road Doha, Qatar Tel : +974 (0) 467 26 49 Fax : +974 (0) 467 47 49 www.hazqatar.com hazdoha@hazqatar.com HAZ METAL DEUTSCHLAND GmbH Leonhard Karl Strasse 29 97877 Wertheim, Germany Tel : +49 (0) 9342 93590 Fax : +49 (0) 9342 935929 www.hazmetal.de info@hazmetal.de

HAZ ASIA PACIFIC PTE LTD

Blk 22 Woodlands Link #01-65 Singapore 738734 Tel: +65 6853 7681 Fax: +65 6752 9582 www.hazapac.com info@hazapac.com

HAZ RUS LTD.

115230, Elektrolitniy Proezd, Dom 3, Stroenie 5, Moscow, Russian Federation Tel : +7 (495) 782 16 28 Fax : +7 (495) 564 87 95 info@hazrus.ru www.hazrus.ru



Always at the forefront of fixing technology, HAZ METAL has earned a reputation as the leaders in fixing systems innovation and is regarded as the one to follow. HAZ METAL fixing systems of today become the standard of tomorrow.

HAZ METAL combines the very latest international technology with its own research and development team to establish a technical excellence within the industry. HAZ METAL readily embraces the responsibility of a major producer and shares its expertise with problem solving solutions.